



## Product Brief

Intel® Server Board  
S5000PSL

# Intel® Server Board S5000PSL

## High-Performance Server Board for Maximum Reliability and Manageability



### Product Overview


Small- and medium-sized businesses today rely on advanced technologies for business applications. Access to the applications that support companies in their quest to maintain their competitive edge require high-performance server boards, with maximum reliability and manageability. Growing businesses need a trusted server solution capable of running a variety of database, file, and messaging applications.

Built on a powerful processor foundation, the Intel® Server Board S5000PSL has the performance and features growing businesses demand. Optional hardware RAID delivers added reliability, excellent data protection, and advanced data management. The S5000PSL optimizes performance and cost by integrating key features, and the variety of configurations provides maximum flexibility and scalability for growing companies.

The S5000PSL supports enterprise-class, high-performance SAS drives, as well as lower-cost SATA drives. More higher-performance PCI Express\* slots provide the expansion headroom businesses need, and the integrated Baseboard Management Controller (BMC) enables manageability while preserving remote management upgrade options. For added flexibility, the S5000PSL is designed to work with both the Intel® Server Chassis SC5400 and the entry-level Intel® Server Chassis SC5299-E.

### Features and Benefits

- 64-bit Multi-core Intel® Xeon® processor improves performance and headroom, and provides scalability and system redundancy with multiple virtual applications.
- Eight fully buffered 533/667 MHz DIMMs increase capacity and performance.
- Dual Gb Ethernet with Intel® I/O Acceleration Technology (Intel® I/OAT) improves application and network responsiveness by moving data to and from server applications faster.
- Four PCI Express\* slots provide the I/O bandwidth needed by servers.
- Integrated server management lowers costs.
- Up to six SATA 3 Gb/s ports.
- Optional 8-port SAS ROMB or optional 4-port SAS supports next-generation enterprise-class SAS drives or SATA drives.



## Intel® Server Board S500PSL Specifications

	<b>S500PSLROMBR (ROMB)</b>	<b>S500PSLSASR (SAS)</b>	<b>S500PSLSATAR (SATA)</b>
<b>Product Code</b>	Intel® Server Chassis SC5400 LX Intel® Server Chassis SC5400 BRP Intel® Server Chassis SC5400 Base Intel® Entry Server Chassis SC5299BRP Intel® Entry Server Chassis SC5299DP	Intel® Server Chassis SC5400 LX Intel® Server Chassis SC5400 BRP Intel® Server Chassis SC5400 Base Intel® Entry Server Chassis SC5299BRP Intel® Entry Server Chassis SC5299DP	Intel® Server Chassis SC5400 LX Intel® Server Chassis SC5400 BRP Intel® Server Chassis SC5400 Base Intel® Entry Server Chassis SC5299BRP Intel® Entry Server Chassis SC5299DP
<b>Intel® Server Chassis Support</b>			
<b>Processor Support<sup>1</sup></b>	Multi-core Intel® Xeon® Processor	Multi-core Intel® Xeon® Processor	Multi-core Intel® Xeon® Processor
<b>Number of Processors Supported</b>	2	2	2
<b>System Bus Speed</b>	667 MHz, 1066 MHz, or 1333 MHz <sup>2</sup>	667 MHz, 1066 MHz, or 1333 MHz <sup>2</sup>	667 MHz, 1066 MHz, or 1333 MHz <sup>2</sup>
<b>Chipset</b>	Intel® Chipset 5000P	Intel® Chipset 5000P	Intel® Chipset 5000P
<b>Independent PCI Buses</b>	6	7	6
<b>Total Slots</b>	6	6	6
<b>Slot Types</b>	2 x PCI Express* x8 2 x PCI Express x4 (x8 Connectors) 1 x PCI-X 100/133 MHz 1 x PCI-X 100 MHz	2 x PCI Express* x8 2 x PCI Express x4 (x8 Connectors) 1 x PCI-X 100/133 MHz 1 x PCI-X 100 MHz	2 x PCI Express* x8 2 x PCI Express x4 (x8 Connectors) 1 x PCI-X 100/133 MHz 1 x PCI-X 100 MHz
<b>Memory Capacity</b>	32GB ECC FBDIMMs (8 DIMMs)	32GB ECC FBDIMMs (8 DIMMs)	32GB ECC FBDIMMs (8 DIMMs)
<b>Integrated ATA</b>	One channel supporting up to two IDE devices	One channel supporting up to two IDE devices	One channel supporting up to two IDE devices
<b>Integrated Serial ATA</b>	Enhanced support for six SATA ports at 3.0 Gb/s with RAID 0, 1, 10 and optional AXXRAKSw5 for RAID 5 <sup>3</sup>	Two SATA ports with support for RAID 0, 1, 10 and optional AXXRAKSw5 for RAID 5 <sup>3</sup>	Enhanced support for six SATA ports at 3.0 Gb/s with RAID 0, 1, 10 and optional AXXRAKSw5 for RAID 5 <sup>3</sup>
<b>SAS</b>	8-Port SAS via included ROMB card (Supports optional upgrade to intelligent RAID 0, 1, 5, 10, 50)	4-Port SAS with Intel® Embedded RAID Technology II providing RAID 0, 1, 10 and optional AXXRAKSw5 for RAID 5 <sup>3</sup>	Not available
<b>Integrated LAN</b>	2 x Intel Gigabit Ethernet connections	2 x Intel Gigabit Ethernet connections	2 x Intel Gigabit Ethernet connections
<b>Integrated Graphics</b>	ATI* with 16MB memory	ATI* with 16MB memory	ATI* with 16MB memory
<b>Server Management Support</b>	Intel® System Management Software and Intel Remote Management Utilities	Intel® System Management Software and Intel Remote Management Utilities	Intel® System Management Software and Intel Remote Management Utilities
<b>Intel® RAID Support</b>	Includes Intel® Integrated Server RAID Module with RAID 0, 1, 10 support. AXXRAK18E and DIMM provide intelligent SAS/SATA RAID 0, 1, 5, 10, and 50 with optional Intel® RAID Smart Battery backup. Refer to <a href="http://support.intel.com/support/motherboards/server/compat_matrix.htm">http://support.intel.com/support/motherboards/server/compat_matrix.htm</a> for up-to-date details on RAID controllers supported by each server board.	Intel® Embedded Server RAID Technology II provides RAID 0, 1, 10 with optional AXXRAKSw5 for RAID 5 <sup>3</sup> . Refer to <a href="http://support.intel.com/support/motherboards/server/compat_matrix.htm">http://support.intel.com/support/motherboards/server/compat_matrix.htm</a> for up-to-date details on RAID controllers supported by each server board.	Intel® Embedded Server RAID Technology II provides RAID 0, 1, 10 with optional AXXRAKSw5 for RAID 5 <sup>3</sup> . Refer to <a href="http://support.intel.com/support/motherboards/server/compat_matrix.htm">http://support.intel.com/support/motherboards/server/compat_matrix.htm</a> for up-to-date details on RAID controllers supported by each server board.

To build your system and get more details on server configurations from Intel visit: [www.intel.com/go/serverconfigurator](http://www.intel.com/go/serverconfigurator)

For more details on the Intel® Server Board S500PSL visit: [www.intel.com/design/servers/boards/s500PSL/index.htm](http://www.intel.com/design/servers/boards/s500PSL/index.htm)

For more information on how to make the Intel® Server Board S500PSL part of your server environment, please contact an Intel® Channel Partner Program participant.

<sup>1</sup> Refer to [www.intel.com/support/motherboards/server/s500psl](http://www.intel.com/support/motherboards/server/s500psl) for up-to-date details on processors supported by each server board.

<sup>2</sup> 1333 MHz support may require updates that may not be available at launch.

<sup>3</sup> Support enabled by installing the AXXRAKSw5 may not be available at launch.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO SALE AND/OR USE OF INTEL PRODUCTS, INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT.

Intel, the Intel logo, Intel. Leap ahead., the Intel. Leap ahead. logo, and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

\*Other names and brands may be claimed as the property of others.

